

L5 ANSWER 470 OF 575 CA COPYRIGHT 2004 ACS on STN  
AN 95:85243 CA  
ED Entered STN: 12 May 1984  
TI Fly ash fluxed flooring composition  
IN Kambor, Hans Ulrich; Wolter, Siegmund; Siebert, Peter; Winklhofer, Helmut;  
Liebmann, Georg  
PA Ger. Dem. Rep.  
SO Ger. (East), 5 pp.  
CODEN: GEXXA8  
DT Patent  
LA German  
IC E04F015-12; C04B031-10  
CC 58-5 (Cement and Concrete Products)  
FAN.CNT 1

	PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
PI	DD 143936	Z	19800917	DD 1979-213086	19790523
PRAI	DD 1979-213086		19790523		

AB An economical fluxed flooring compn. of easy workability and low  
cement content is composed of fly ash 7-36,  
cement 3-21, 0-4 mm sand 40-85, water 5-22, and concrete  
plasticizer 0.1-0.8 wt.%. The product is transported through  
pipes and easily applied on a floor. The strength of this flooring compn.  
is generally higher than that of anhydrite fluxed compns.  
ST flooring compn fly ash sand  
IT Sand  
RL: USES (Uses)  
(flooring compn., contg. fly ash and cement  
)